



# Asserta Midi Electronic Sounder

**L G M**  
**PRODUCTS**



135mm



## SPECIFICATION

Voltage Options	Current mA*	Weight Kg.	Sound output *	@ 24vdc: 108 dB(A)
115/230 Vac	22mA @ 230Vac	1.00Kg	<b>IP Rating</b>	66
9 - 60 Vdc	24mA @ 24Vdc	1.00Kg	<b>Alarm tones</b>	32
			<b>Alarm Stages</b>	2
			<b>Volume Control</b>	Yes
			<b>Cable entry</b>	M20 Knockouts
			<b>Op temp</b>	DC: -25°C to +70°C AC: -10°C to + 60°C
			<b>Body Material</b>	ABS
			<b>Body Colour</b>	Red or Grey

**\*NOTE:** Sound output and current consumption values are based on the 800 to 1000 Hz alternating signal, the standard UK fire alarm tone. These values will vary for other alarm tones

**ORDER CODE: ASmidi/Voltage/Colour**

**LGM PRODUCTS LTD**  
**UNIT 18 RIVERSIDE INDUSTRIAL ESTATE**  
**FARNHAM**  
**SURREY GU9 7UG**  
**UNITED KINGDOM**

**TEL +44 (0) 1252 725257**  
**FAX +44 (0) 1252 727627**  
**E-mail sales@Lgmproducts.com**  
**www.Lgmproducts.com**