

Discovery Marine

Multi Sensor Combined Fire Detector

L G M
PRODUCTS



Multi Sensor Technology

The Multi Sensor detector combines inputs from optical and heat sensors and processes them using a sophisticated algorithm. When polled by the control panel it returns a signal which is determined by combined responses from both optical and heat sensors.

The XP95 Multi-Sensor detector is designed to be sensitive to a wide range of fires and may be used in place of an ionisation detector in many instances.

SPECIFICATION

Electrical

Voltage	14 -28 Vdc
Supply Wiring	2 wire polarity insensitive
Communication Protocol	Apollo Discovery 5-9 V
Power up time	10 seconds max
Switch on surge current @ 24 Vdc	1 mA
Quiescent current	500µA average 650µA peak
Alarm Current with LED indicator on	3.5mA
Alarm Indicator	2 x LED
Alarm Indicator	LED indicator with 360 deg visibility
Sampling Frequency	Every 1 second

Mechanical

Detector body material	Polycarbonate
Base material	Polycarbonate
Detector & base colour	White
Max RH	98% no condensation
Storage temp deg C	-30 to +80 deg C
Operating temp deg C	-20 to +60 deg C No condensation / icing
Wind Speed	Unaffected by wind
IP rating	43
Detector & base dims	Diameter 100mm Height 58mm (detector in base)
Detector + base weight	0.16 Kg net 0.25 Kg gross packed

Note: For Intrinsically Safe (I.S.) analogue addressable detectors use the XP95 series of detectors

See page 2 for approvals, part numbers and accessories

LGM PRODUCTS LTD
UNIT 18 RIVERSIDE INDUSTRIAL ESTATE
FARNHAM
SURREY GU9 7UG
UNITED KINGDOM

TEL +44 (0) 1252 725257
FAX +44 (0) 1252 727627
E-mail Sales@Lgmproducts.com
www.Lgmproducts.com

Discovery Marine

Multi Sensor

Combined Fire Detector Pg 2

L G M
PRODUCTS

Discovery Marine multi sensor type smoke detectors carry the following marine approvals:

- LR Lloyd's Register of Shipping
- MCA Maritime and Coastguard Agency
- ABS American Bureau of Shipping
- BV Bureau Veritas
- DNV Det Norske Veritas
- GL Germanischer Lloyd
- CCS China Classification Society

Accessories and part numbers

Multi Sensor Detector	58000-700MAR
Std base + address card	45681-210MAR
Isolating base	45681-321MAR
Universal conduit box	45681-204-APO
Backplate	45681-233APO
Deckhead mounting box aluminium PG19 entries*	29600-131
Deckhead mounting box aluminium M20 entries*	29600-139
Deckhead mounting box plastic PG19 entries	29600-196
Deckhead mounting box plastic M20entries*	MBB-1
Base cover	45681-380APO

* Data sheet available

LGM PRODUCTS LTD
UNIT 18 RIVERSIDE INDUSTRIAL ESTATE
FARNHAM
SURREY GU9 7UG
UNITED KINGDOM

TEL +44 (0) 1252 725257
FAX +44 (0) 1252 727627
E-mail Sales@Lgmproducts.com
www.Lgmproducts.com