

Discovery

Optical Smoke Detectors

L G M
PRODUCTS



Key Features

- Rejection of transient signals
- Flashing LED option
- Five response modes for ease of optimisation to changing environments
- Drift compensation to ensure constant sensitivity
- Four bytes of user programmable non-volatile memory
- Alarm flag for fast alarm reporting
- 360° visibility in alarm
- Compatible with XP95 systems

SPECIFICATION

Electrical

Voltage	14 -28 Vdc
Supply Wiring	2 wire polarity insensitive
Communication Protocol	Apollo Discovery 5-9 V
Power up time	10 seconds max
Switch on surge current @ 24 Vdc	1 mA
Average quiescent current	400µA 650µA peak
Alarm Current with LED indicator on	3.4mA
Alarm Indicator	2 x LED indicator
Sampling Frequency	Every 1 second

Mechanical

Detector body material	Polycarbonate
Base material	Polycarbonate
Detector & base colour	White
Max RH	98% no condensation
Storage temp deg C	-30 to +80 deg C
Operating temp deg C	-20 to +60 deg C
Wind Speed	Unaffected by wind
IP rating	43
Detector & base dims	Diameter 100mm Height 50mm
Detector + base weight	0.16 Kg net 0.25 Kg gross packed

Detector Part No

58000-600APO

Base Type

Std base + address	45681-210APO
Isolating base	45681-321APO
Low power relay base	45681-242APO

Base Part No

APPROVALS: LPCB, VdS

Note: For Intrinsically Safe (I.S.) analogue addressable detectors use the XP95 series of detectors

LGM PRODUCTS LTD
UNIT 18 RIVERSIDE INDUSTRIAL ESTATE
FARNHAM
SURREY GU9 7UG
UNITED KINGDOM

TEL +44 (0) 1252 725257
FAX +44 (0) 1252 727627
E-mail Sales@Lgmproducts.com
www.Lgmproducts.com